



## **Features**

### Flexible applications

- · Highly efficient liquid-cooled cooling and heating for extreme environments
- · Compact design with Back-to-back layouts for a reduced footprint

## Efficient charging and discharging

 $\cdot$  Meet high-rate charging and discharging scenarios, with a maximum continuous power of up to 1P

#### Safety and reliability

- · Electrical safety management, overcurrent fast-breaking and arc extinguishing protection
- · Pack-level fire protection and prediction of thermal runaway risk

#### **Convient O&M**

- · One-click system upgrade and unified management
- · Cloud-based monitoring allows for the quick identification of faults and reduce staff effort



ZOE Energy Storage, a pioneer in integrating investment, operation of energy storage stations, and the R&D, manufacturing, and sales of energy storage systems, has its global headquarters in Shanghai. With its R&D center in Jiangsu and joint laboratories established with top universities and international institutions, ZOE advances the development and application of energy storage technology. The company operates 14GWh intelligent energy storage factories in Jiangxi and Sichuan and has established the ZOE Digital Center in Shanghai. Leveraging outstanding R&D capabilities and innovative approaches, ZOE delivers both standardized and tailored energy storage solutions, bridging grids and senarcing for organized electricity uses and belanced loads.

As a subsidiary of the ZOE Energy Group, ZOE Energy Storage contributes to the group's overarching mission. Founded in 2013, ZOE Energy Group is a high-tech enterprise dedicated to the development, investment, and management of new energy projects. Targeting carbon neutrality, the Group has developed 23 utility-scale solar projects with a combined capacity of 3.53GW and is progressing with wind, photovoltaic projects of 1.23GW. With a cumulative investment exceeding \$4.4 billion, the Group has realized an annual compound growth rate of 183%, underscoring its commitment to sustainable energy development.



# • P 1300-1H P1313L1H-A-EU 1.26MW/ 1.313MWh

Battery Data	
Cell type	LFP
Rated capacity	285 Ah
Serial-parallel type	6P240S
Rated capacity per pack	43.776 kWh
Pack number	6*5
System rated energy capacity	1313.28 kWh
Rated DC voltage	768 V
Rated DC voltage range	672~864 V
Rated DC current	1710 A
AC Data	
Rated AC power	1260 kW
Rated AC voltage	400 Vac
Rated frequency	50/60 Hz
Rated AC current	1818 A
Max. AC current	2004 A
AC wiring type	3W/ N+PE
Power factor	-1~1
General Data	
DOD	90%
Noise	≤80dB
Protection degree	IP 54
Cooling method	Liquid cooling/ heating
Fire suppression system	NOVEC 1230 + Aerosol
Operating temperature range	$-30 \sim 55$ °C ( $> 45$ °C derating)
Relative humidity	5% ~ 95% RH
Max.working altitude	2000 m
Display	Web/ LED/ LCD
COM interfaces	RS485/ Ethernet
Dimensions (L*W*H)	6058*2438*2591 mm
Weight	20 T



